



OUTDOOR PANEL

AA-14FB

INTUITIVE, POWERFUL SOLUTION The AA14 is an outdoor intercom entry station supporting up to 10k entries. The 10" touch screen has an intuitive search feature allowing visitors to quickly find and communicate with intended parties. Visitor calls can be answered on a mobile app, phone, in-suite tablet or routed to a SIP phone system. As an entry station, access can be granted to visitors with our mobile app or by pressing a number on the phone key pad. For residents in the building, entry can be gained by using a card credential or PIN.

1.3 MP Camera
Day/Night



Full Duplex Audio

10" TFT Screen
Full Touchscreen



6 LED Backlight



26-Bit Weigand Card
Reader

basIP



Searchable Directory Listing - Up to 10,000 entries! · IP65 · Cloud or Stand-alone · SIP
Day/Night · Motion Sensor · Integrated with Access Control & VMS · ONVIF Camera
Browser Supported · IK7 - Vandal Resistant

SPECIFICATIONS:

MAIN FEATURES	
Panel Type	Multi-apartment
Display	10" TFT, color with backlight and heated under plate
Keypad	Sensor
Camera	1/4"
Angle	90° horizontal x 64° vertical
Resolution	1.3 Mp.
Output Video	HD (1280 × 720), H.264 Main Profile
Night Backlight	6 LEDs
Light Sensitivity	0.01 Lux
Protection Class	IP65
Working Temperature	-40 – +65 °C
Power Consumption	6,5 W, in standby – 3,6 W
Power Supply	+12 V DC Sold Separately
Body	Aluminum
Colors	Silver
Dimensions for Installation	400 × 180 × 45 mm
Size of the Panel	375 × 172 × 60 mm.
Installation	Flush wall mount

FUNCTIONALITY	
Paging	Station to station, group and overhead speaker
Interface	Multi-language graphical and WEB interface
Lock Opening	<ul style="list-style-type: none"> - By means of a monitor - By the code - By an access card - From API
Access Control Integration	WIEGAND-26+ output
Shortcut Buttons	Concierge Button
Number of Call Melodies	4 polyphonic melodies, ability to customize melodies for different actions
Authentication	Separate password for settings, WEB - interface and RTSP stream
Talking Mode	Full Duplex
Additionally	<ul style="list-style-type: none"> - Software Link support - SIP P2P - Built-in relay - Proximity sensor - Open API

ADDITIONS		Image
Surface Mount	BR-AA14	
Flush Mount Included		
supported on legacy 2-wire systems with our SW-series conversion kits	SW-02 SW-08 SW-10	 

DIMENSIONS: (not to scale)

