



OUTDOOR PANEL

AV-01KD

AV-01D

FLEXIBLE SECURITY, AFFORDABLE OPTIONS The AV01KD is an outdoor intercom entry system that can operate in two modes – individual and multi apartment. In the individual mode, the keypad can be used to enter a PIN for opening the lock, and with the dedicated call button, visitors can make a direct call. In multi apartment mode, the keypad can be used to dial the intended parties. Visitor calls can be answered on a mobile app, phone, in-suite tablet or routed to a SIP phone system. As an entry station, access can be granted to visitors with our mobile app or by pressing a number on the phone key pad.



6 LED Backlight · Full Duplex Audio · 1P 720P Camera Resolution · IP65
PoE Input Power · Supports up to 10k Entries · Cloud or Stand-alone
Integrated with Acces Control & VMS · ONVIF Camera · Browser Supported

SPECIFICATIONS:

MAIN FEATURES	
Panel Type	Individual
Display	No
Camera	1/4", adjustable camera angle by 15°
Angle	100° horizontal x 58° vertical
Resolution	1 Mp.
Output Video	720p (1280 × 720), H.264 Main Profile
Night Backlight	6 LEDs
Light Sensitivity	0.01 Lux
Protection Class	IP65
Working Temperature	-40 – +65 °C
Power Consumption	5,5 W, in standby – 2,5 W
Power Supply	+12 V DC, PoE 802.3af
Body	Metallic
Colors	Titanium Gray
Dimensions for Installation	104 × 180 × 60 mm
Size of the Panel	115 × 190 × 45 mm
Installation	Flush, surface with BR-AV Bracket

FUNCTIONALITY	
Paging Options	Station to station, group and overhead speaker
Interface	Multi-language graphical and WEB interface
Lock Opening	- By means of a monitor - From the BAS-IP Intercom application - By PIN code
ACS Integration	No
Shortcut Buttons	1 mechanical call button, keypad
Authentication	Separate password for settings, WEB - interface
Talking Mode	Duplex
Additionally	- SIP P2P - Built-in relay

ADDITIONS		Image
Surface Mount	BR-AV	
Flush Mount Included		
supported on legacy 2-wire systems with our SW-series conversion kits	SW-02 SW-08 SW-10	

DIMENSIONS: (not to scale)

